

"Miami-Dade County Product Control Approved"
Hurricane Shutters and FBC Decorative Shutters
www.bsishutters.com Email: bsishutters@juno.com
Patent No: U.S. 6,996,934 B2 & 7,131,480 B2

2841 Shoreview Drive, Naples FL 34112

fice **239-774-2025** Fax 239-774-9483

Miami-Dade County Product Control Approved, Bahama & Colonial Shutters, TAS 201, 202, 203, NOA's @ www.miamidade.gov/building FBC Engineered & Certified Decorative Shutters, TAS 202 & ASTM E330-Uniform Static, ASCE 7-10 Wind Loads - Components & Cladding

Product Description Fixed Shutter Panel

Decorative Shutter Panel by BSI

Briscoe Shutters Inc. (BSI) is dedicated to providing the highest quality and standards in the design and production of our FBC Tested and Certified Decorative Shutter Systems and "Miami-Dade County Product Control Approved" Bahama, Colonial, and Bahama over Colonial Hurricane Shutter Systems.

No Build out Frame is required for the Decorative Shutter Systems (optional Build Out Frame, additional fee)

Fixed Decorative Shutter Panel

Attaches between columns or openings at the head (top) and/or optional @ jambs (sides), depends on the size of shutter leafs

- 1 Decorative shutters do not have a build out frame, the shutter attaches to the structure directly
- 2 Fastening the shutter to the building structure with custom designed brackets for each application
- 3 The perpendicular opening between each fixed slat is 1/8"
- 4 The opening in-between each fixed slat at the 45-degree angle is 1/2"

We offer a 10-Year Warranty on all of our products

Shutter Frame Profile

1" Frame (standard)

2" Finished frame profile (1" frame + 1" weld guide or spacer)

2" Frame (additional fee)

3" Finished frame profile (2" frame + 1" weld guide or spacer)

Technical Data

Decorative Shutter Product Description with 1" Frame, 2" Wide Finished Frame Profile, (standard),

Material

ASTM, Aluminum Alloy, 6063-T53, and 6005; $1" \times 1-1/2" \times 1/8"$ Rectangular Tube, $1" \times 1" \times 1/8"$ Square Tube, $1/4" \times 1"$ Flat Bar, $1" \times 1" \times 1/8"$ Angle, $1" \times 1/2"$ Flat Bar, $2" \times 1/8"$ Flat Bar @ Optional Vertical Mullion, Aluminum Brackets custom made for each application

Anchors

Concrete Block or Wood - 1/4" Stainless Steel Masonry Fasteners, Steel - 10-24 Tek Screws

Assembly

Shutters are custom measured, designed, and manufactured for each opening. Mitered corners and butt connections, welded then sanded to a smooth finish. We use a stamped weld guide to maintain exact opening tolerances, the slats are welded to the shutter frames and optional mullion(s), then the back cover is installed to conceal the welds.

Shutter Finish:

Super Durable Powder Coating: Color Selections from RAL - Color Charts, some colors subject to additional fee